

Product Data Sheet



Peppercorn Granite



Description

| | |
|---------------------|---|
| Appearance | Medium to coarse grained crystalline rock |
| Finishes | Flamed, Fine Picked, Honed or Polished. |
| Governing Standards | BS EN 1341/1342/1343 : 2001 |
| Quarry of Origin | Shandong, P.R.C |

Physical Properties

| | |
|--------------------------|-----------------------------------|
| Work Dimensions | To customers' specification |
| Tolerances on Dimensions | Class 2 |
| Compressive Strength | 175 MPa |
| Flexural Strength | 19.2 MPa |
| Material Density | 2850kg/m ³ (typically) |
| Slip Resistance | 58 Wet – TLR 71 Dry – TLR |
| Abrasion Resistance | 17.20mm |
| Water Absorption | 0.29% |

Supply

| | |
|------------|---|
| Crate Size | Maximum 1.8 tonnes. Approx. size 1.0 x 1.0 x 0.80 high |
| Packaging | Wooden crates, suitable for stacking and transportation by fork lift. |

Cleaning and Maintenance

Use of mechanical cleaning, especially wire brushing, should be avoided as this will reduce, over time, skid resistance. Washing with clean water should be adequate but not pressure jetting as this could eventually remove the jointing material.

BBS Granite Concepts Ltd
Kimcote House, Walton Road,
Kimcote, Leicestershire
LE17 5RU
Tel: 01455 559474
Email: sales@bbsgraniteconcepts.com
www.bbsnaturalstone.com



BBS Brick & Stone Ltd
Lower Wharfe House,
Wharfebank Mills, Otley, Yorkshire
LS21 3JP
Tel: 01924 241 100
Email: sales@bbsgraniteconcepts.com
www.bbsnaturalstone.com